



BALE CLAMP

Efficiently handles any material in bale form — cotton, textiles, scrap/rags, etc.

- **Lightweight Design** — slide channels are made of long-life aluminum alloy and reinforced for strength.
- **Minimal A.E.T.** — low attachment effective thickness dramatically reduces lost load, improves lift truck balance.
- **Interchangeable components extent part life, economy** — channels and slide bars can be switched out side-to-side and inverted for longer wear; can also be replaced individually as needed.
- **Grooved Gussets** — give clamp the maximum gripping force.
- **Available in a Variety of Operating Ranges** — to handle loads from 3,000 to 5,000 pounds.
- **Flow divider** — provides consistent equal arm movement.

BALE CLAMP

Single Hydraulic Function

| Model No | Capacity (w/ 24" L.C. (Lbs.)) | Opening Range (In.) | Mounting ITA Hook | Arm Width (In.) | Arm Length (In.) | Body Width (In.) | A.E.T. (In.) | C.G. (In.) | Weight (Lbs.) |
|----------|-------------------------------|---------------------|-------------------|-----------------|------------------|------------------|--------------|------------|---------------|
| BC31A | 3000 | 18-66 | II | 15 | 27 | 35 | 4.25 | 6.9 | 700 |
| BC32A | 3000 | 18-66 | II | 15 | 32 | 35 | 4.25 | 8.6 | 750 |
| BC33A | 3000 | 18-66 | II | 15 | 36 | 35 | 4.25 | 11.6 | 780 |
| BC41A | 4000 | 18-66 | II | 18 | 27 | 36 | 5.25 | 6.7 | 790 |
| BC43A | 4000 | 18-66 | II | 18 | 32 | 36 | 5.25 | 8.8 | 825 |
| BC45A | 4000 | 18-66 | II | 18 | 36 | 36 | 5.25 | 9.1 | 850 |
| BC51A | 5000 | 20-92 | II | 18 | 27 | 60 | 5.50 | 6.9 | 925 |
| BC51B | 5000 | 20-92 | III | 18 | 27 | 60 | 5.50 | 6.9 | 925 |
| BC52A | 5000 | 20-92 | II | 18 | 32 | 60 | 5.50 | 8.1 | 975 |
| BC52B | 5000 | 20-92 | III | 18 | 32 | 60 | 5.50 | 8.1 | 975 |
| BC53A | 5000 | 20-92 | II | 18 | 36 | 60 | 5.50 | 9.1 | 1025 |
| BC53B | 5000 | 20-92 | III | 18 | 36 | 60 | 5.50 | 9.1 | 1025 |
| BC54A | 5000 | 40-120 | II | 18 | 36 | 80 | 5.50 | 8.4 | 1125 |
| BC54B | 5000 | 40-120 | III | 18 | 36 | 80 | 5.50 | 8.4 | 1125 |

Installation of backrest may be required by OSHA or local regulations.

SIDE SHIFTING BALE CLAMP

Dual Hydraulic Function

| Model No | Capacity (w/ 24" L.C. (Lbs.)) | Opening Range (In.) | Mounting ITA Hook | Arm Width (In.) | Arm Length (In.) | Body Width (In.) | A.E.T. (In.) | C.G. (In.) | Weight (Lbs.) |
|----------|-------------------------------|---------------------|-------------------|-----------------|------------------|------------------|--------------|------------|---------------|
| SBC31A | 3000 | 18-66 | II | 15 | 27 | 35 | 4.25 | 6.9 | 700 |
| SBC32A | 3000 | 18-66 | II | 15 | 32 | 35 | 4.25 | 8.6 | 750 |
| SBC33A | 3000 | 18-66 | II | 15 | 36 | 35 | 4.25 | 11.6 | 780 |
| SBC41A | 4000 | 18-66 | II | 18 | 27 | 36 | 5.25 | 6.7 | 790 |
| SBC43A | 4000 | 18-66 | II | 18 | 32 | 36 | 5.25 | 8.8 | 825 |
| SBC45A | 4000 | 18-66 | II | 18 | 36 | 36 | 5.25 | 9.1 | 850 |
| SBC51A | 5000 | 20-92 | II | 18 | 27 | 60 | 5.50 | 6.9 | 925 |
| SBC51B | 5000 | 20-92 | III | 18 | 27 | 60 | 5.50 | 6.9 | 925 |
| SBC52A | 5000 | 20-92 | II | 18 | 32 | 60 | 5.50 | 8.1 | 975 |
| SBC52B | 5000 | 20-92 | III | 18 | 32 | 60 | 5.50 | 8.1 | 975 |
| SBC53A | 5000 | 20-92 | II | 18 | 36 | 60 | 5.50 | 9.1 | 1025 |
| SBC53B | 5000 | 20-92 | III | 18 | 36 | 60 | 5.50 | 9.1 | 1025 |
| SBC54A | 5000 | 40-120 | II | 18 | 36 | 80 | 5.50 | 8.4 | 1125 |
| SBC54B | 5000 | 40-120 | III | 18 | 36 | 80 | 5.50 | 8.4 | 1125 |

Installation of backrest may be required by OSHA or local regulations.
Other arm sizes available upon request.



201 W. Oklahoma Ave.
(580) 227-3711

Fairview, OK 73737
FAX 580-227-2165