



DUMPER UPENDER

Simplifies big dumping/upending chores with operator-controlled hydraulic convenience

- **Automatically Handles Many Needs** — able to quickly dump or slowly pour powders, liquids, chemicals, scrap, waste and other material from steel and fiber drums, special hoppers, boxes, trays or wire baskets.
- **Operator-Controlled Convenience** — without leaving his seat, the driver can safely set and monitor material flow.
- **Specialized Clamping Pads Available** — standard drum pads (10"W X 18"H) handle both steel and fiber drums; OPTIONAL PADS to handle many other applications: dumping carboys, wire baskets, boxes;

upending rolls, bales, and other objects from vertical to horizontal position.

- **Equal Arm Movement, Standard** — assures that the clamping pads grip the load at the same time. Side-shifting is available as an option.
- **180° Forward Tilt** — maximum operator control of dumping process and excellent visibility.
- **Saves Time, Cuts Costs, Prevents Accidents and Injuries**
- **Versatile** — remove dumper pads to use as a standard fork clamp.

DUMPER-UPENDER* Dual Hydraulic Function

Model No.	Capacity w/Forks @ 24" L.C. (Lbs.)	Opening Range w/ Dumpers (In.)	Mounting ITA Hook	Fork Length (In.)	Lifting Capacity w/Dumpers (Lbs.)	Body Width (In.)	O.A.C.L. (In.)	C.G. (In.)	Weight (Lbs.)
DUC31A	3000	11-59	II	36	2000	35	32.5	9.0	700
DUC32A	3000	11-59	II	42	1800	35	38.5	12.0	725
DUC33A	3000	11-59	II	48	1500	35	44.5	14.0	750
DUC41A	4000	11-59	II	36	3000	36	33.5	8.6	830
DUC42A	4000	11-59	II	42	2500	36	39.5	11.0	850
DUC43A	4000	11-59	II	48	2000	36	45.5	13.0	870
DUC51A	5000	13-65	II	36	4000	40	34.5	9.6	1250
DUC52A	5000	13-65	II	42	3500	40	40.5	11.3	1270
DUC53A	5000	13-65	II	48	3000	40	46.5	13.5	1290

*Add 7 inches for opening range without Dumpers

SIDE-SHIFTING DUMPER-UPENDER* Triple Hydraulic Function

Model No.	Capacity w/Forks @ 24" L.C. (Lbs.)	Opening Range w/ Dumpers (In.)	Mounting ITA Hook	Fork Length (In.)	Lifting Capacity w/Dumpers (Lbs.)	Body Width (In.)	O.A.C.L. (In.)	C.G. (In.)	Weight (Lbs.)
SDUC31A	3000	11-59	II	36	2000	35	32.5	9.0	700
SDUC32A	3000	11-59	II	42	1800	35	38.5	12.0	725
SDUC33A	3000	11-59	II	48	1500	35	44.5	14.0	750
SDUC41A	4000	11-59	II	36	3000	36	33.5	8.6	830
SDUC42A	4000	11-59	II	42	2500	36	39.5	11.0	850
SDUC43A	4000	11-59	II	48	2000	36	45.5	13.0	870
SDUC51A	5000	13-65	II	36	4000	40	34.5	9.6	1250
SDUC52A	5000	13-65	II	42	3500	40	40.5	11.3	1270
SDUC53A	5000	13-65	II	48	3000	40	46.5	13.5	1290

* Add 7 inches for opening range without dumper
* Pressure regulator valve is recommended for all applications



201 W. Oklahoma Ave.
(580) 227-3711

Fairview, OK 73737
FAX 580-227-2165