



MULTI-PURPOSE CLAMPS

WITH RUBBER-COVERED ARMS ROTATING OR RIGID

Moves unit loads of cartons, crates, bales, rolls and boxes without the use of pallets.

- **Available in single hydraulic function** — maneuvers loads in most material handling applications.
- **Side-Shifting double hydraulic function** — flexible, rubber-covered gripper arms move in unison from side to side, eliminating much of the need to reposition the lift truck every time the load is lifted and released.
- **Designed for long-life, maximum payload** — lightweight body reduces lost load center. Rubber gripper pads are easily replaced.
- **Interchangeable, reversible components** — aluminum alloy channel bars can be switched from one side to the other, and inverted, to balance out wear, extend part life.
- **Optimal load shape control** — built-in camber and toe-in help position and square the load while preventing sag.
- **Individual arm movement** — optional feature for applications requiring one arm to move alone to enter a stack without repositioning the truck.
- **360° rotating clamp** — optional feature; utilizes advanced design, state-of-the-art, lightweight Waldon® Rotator for minimum lost load center.
- **Flow divider** — provides consistent equal arm movement.

See product specifications on reverse side



201 W. Oklahoma Ave.
(580) 227-3711

Fairview, OK 73737
FAX 580-227-2165



Multi-Purpose Clamp With Rubber-Covered Arms

Non-Side Shifting Model No.	Side Shifting Model No.	Capacity @ 24" L.C. (Lbs.)	Opening Range (In.)	Mounting ITA Hook	Arm Length (In.)	Arm Height (In.)	Body Width (In.)	A.E.T. (In.)	C.G. (In.)	Weight (Lbs.)
MPC31	SMPC31	3000	22-70	II	27	18	35	6.25	9.1	685
MPC32	SMPC32	3000	22-70	II	32	18	35	6.25	11.3	785
MPC33	SMPC33	3000	22-70	II	36	18	35	6.25	13.1	850
MPC41	SMPC41	4000	22-70	II & III	27	18	36	7.25	8.7	800
MPC42	SMPC42	4000	22-70	II & III	27	18	36	7.25	8.7	800
MPC42	SMPC42	4000	22-70	II & III	32	18	36	7.25	10.9	900
MPC43	SMPC43	4000	22-70	II & III	36	18	36	7.25	12.6	965
MPC44	SMPC44	4000	22-70	II & III	42	18	36	7.25	15.6	1025
MPC51	SMPC51	5000	24-76	II & III	27	18	40	7.50	9.0	925
MPC52	SMPC52	5000	24-76	II & III	32	18	40	7.50	11.1	1025
MPC53	SMPC53	5000	24-76	II & III	36	18	40	7.50	12.9	1095
MPC54	SMPC54	5000	24-76	II & III	42	18	40	7.50	15.9	1150

Installation of backrest may be required by OSHA or local regulations.

Add the following suffix to model for mounting class desired

A - ITA Class II

B - ITA Class III

RB - Round bar mounting (customer to supply mounting information)

Rotating Multi-Purpose Clamp With Rubber-Covered Arms

Dual Hydraulic Function

Model No.	Capacity @ 24" L.C. (Lbs.)	Opening Range (In.)	Mounting ITA Hook	Arm Length (In.)	Arm Height (In.)	Body Width (In.)	A.E.T. (In.)	C.G. (In.)	Weight (Lbs.)
RMPC31	3000	22-70	II & III	27	18	37	9.25	8.44	1085
RMPC32	3000	22-70	II & III	32	18	37	9.25	10.23	1185
RMPC33	3000	22-70	II & III	36	18	37	9.25	11.68	1250
RMPC41	4000	22-70	II & III	27	18	37	10.5	8.55	1200
RMPC42	4000	22-70	II & III	32	18	37	10.5	10.33	1300
RMPC43	4000	22-70	II & III	36	18	37	10.5	11.72	1365
RMPC44	4000	22-70	II & III	42	18	37	10.5	14.05	1425
RMPC51	5000	24-76	II & III	27	18	37	10.75	9.08	1325
RMPC52	5000	24-76	II & III	32	18	37	10.75	10.81	1425
RMPC53	5000	24-76	II & III	36	18	37	10.75	12.30	1495
RMPC54	5000	24-76	II & III	42	18	37	10.75	14.66	1550

0 degree mounting is standard 4-degree optional at no extra charge
Installation of backrest may be required by OSHA or local regulations

Add the following suffix to model for mounting class desired

A - ITA Class II

B - ITA Class III

RB - Round bar mounting (customer to supply mounting information)

Consult factory for special opening ranges

Consult factory for special mounting other than ITA



201 W. Oklahoma Ave.
(580) 227-3711

Fairview, OK 73737
FAX 580-227-2165