



ROTATOR

360° Freedom-of-movement for virtually any rotating operation — dumping, inverting, pouring, etc.

- **Thin, Compact, Lightweight Design** — permits a smaller truck to move bigger loads.
- **Zero-Degree Mounting** — results in less lost load than standard four-degree mounts.
- **Turns Smoothly, Evenly** — precision ring gear is supported by injected, sealed ball bearings.
- **Precision Casting Seals Out Corrosion** — completely eliminates infiltration of foreign particles and rust, for longer life even in harsh environments.
- **Direct-Drive Hydraulic Motor** — delivers high torque output without backlash.
- **Motor Mounts On Either Side** — reduces plumbing problems, simplifies installation.
- **Large Center Hole, Cut-Out Sides** — aid driver visibility and accuracy.
- **Available in a Wide Range of Load Capacities**
- **Fewer Parts** — less chance of breakdown; cuts maintenance and downtime.

360 Degree Rotator With Fork Bars Single Hydraulic Function

Model No.	Capacity @ 24" L.C. (Lbs.)	Rotator Width (In.)	Mounting ITA Hook	Height (In.)	Carriage Width (In.)	A.E.T. (In.)	C.G. (In.)	Torque @ 2000 PSI (Lbs.)	Approx. Weight
RTM30	3-4000	37.5	II	26.0	37	4.6	2.4	41,500	525
RTM50	5000	37.5	II	26.0	37	4.6	2.4	54,000	535
RTM60	6000	37.5	III	26.0	42	5.0	2.8	80,500	650
RTM90	9000	43.5	III	31.0	43	5.6	3.1	88,500	890
RTM110	11000	43.5	IV	34.5	47	5.7	3.3	98,500	1145
RTM176	17600	47.25	IV	36.2	59	7.3	3.9	177,000	Consult Factory

(A) All figures without forks (B) Wider carriage plate, consult factory



201 W. Oklahoma Ave.
(580) 227-3711

Fairview, OK 73737
FAX 580-227-2165