



CARTON CLAMP

Handles unpalletted loads of cartons and boxes with hydraulic efficiency and ease.

- **Eliminates Problems Associated With Wood Pallets** — including cost, repair, loss, and storage space; clamped loads stack faster, tighter, higher.
- **Slim, Lightweight Design** — thin aluminum arms slide between boxes with minimal damage; bonded rubber facings provide maximum gripping force.

- **"National Rubber" Pads Standard**
- **Standard ITA Mountings or Quick Release Mountings Offered at No Additional Charge**
- **Equal Arm Movement Standard** — a combination of side-shift permits simultaneous pad opening/closing.
- **Pilot-Operated Check Valves** — ensure retention of clamping force at all times.
- **Pad Articulation, Toe-in and Camber Adjustments Standard** — added features increase handling efficiency and ease.
- **Flexibility in Handling Different-Sized Loads** — opening range from 22 to 76 inches; weight capacities vary from 2,500 to 4,500 pounds.

*A pressure regulator valve is recommended for any Carton Clamp application.

SIDE SHIFTING CARTON CLAMP Double Hydraulic Function

Model No.	Capacity @ 24" L.C. (Lbs.)	Opening Range (In.)	Mounting ITA Hook	Arm Length (In.)	Arm Height (In.)	Body Width (In.)	A.E.T. (In.)	C.G. (In.)	Weight (Lbs.)
SCC21A	2500	22-70	II	36	48	35	4.25	15.8	1150
SCC22A	2500	22-70	II	40	48	35	4.25	16.8	1210
SCC23A	2500	22-70	II	42	48	35	4.25	17.0	1250
SCC24A	2500	22-70	II	44	48	35	4.25	17.1	1290
SCC25A	2500	22-70	II	46	48	35	4.25	17.2	1330
SCC26A	2500	22-70	II	48	48	35	4.25	18.0	1370
SCC351A	3500	22-70	II	40	48	36	5.25	17.8	1310
SCC351B	3500	22-70	III	40	48	36	5.25	17.9	1320
SCC352A	3500	22-70	II	42	48	36	5.25	18.1	1350
SCC352B	3500	22-70	III	42	48	36	5.25	18.1	1360
SCC353A	3500	22-70	II	44	48	36	5.25	18.3	1390
SCC353B	3500	22-70	III	44	48	36	5.25	18.3	1400
SCC354A	3500	22-70	II	46	48	36	5.25	18.5	1430
SCC354B	3500	22-70	III	46	48	36	5.25	18.5	1440
SCC355A	3500	22-70	II	48	48	36	5.25	19.0	1470
SCC355B	3500	22-70	III	48	48	36	5.25	19.0	1480
SCC51A	4500	24-76	II	40	48	40	5.50	18.2	1435
SCC51B	4500	24-76	III	40	48	40	5.50	18.3	1445
SCC52A	4500	24-76	II	42	48	40	5.50	18.5	1475
SCC52B	4500	24-76	III	42	48	40	5.50	18.5	1485
SCC53A	4500	24-76	II	44	48	40	5.50	18.7	1510
SCC53B	4500	24-76	III	44	48	40	5.50	18.7	1520
SCC54A	4500	24-76	II	46	48	40	5.50	18.9	1555
SCC54B	4500	24-76	III	46	48	40	5.50	18.9	1565
SCC55A	4500	24-76	II	48	48	40	5.50	19.1	1600
SCC55B	4500	24-76	III	48	48	40	5.50	19.1	1610

- (A) Equal arm movement with integral side-shift standard.
 (B) Bolt on backrest standard.
 (C) Arms have replaceable aluminum pads with bonded rubber facing
 (D) Consult factory for special arm sizes or opening ranges.
 (E) Pressure regulator Valve recommended on all Carton Clamps

