

The Waldon Dump Upender simplifies big dumping/upending chores with operator-controlled hydraulic convenience.

- **Automatically Handles Many Needs** — able to quickly dump or slowly pour powders, liquids, chemicals, scrap, waste and other material from steel and fiber drums, special hoppers, boxes, trays or wire baskets.
- **Operator-Controlled Convenience** — without leaving his seat, the driver can safely set and monitor material flow.
- **Specialized Clamping Pads Available** — standard drum pads (10"W x 18"H) handle both steel and fiber drums; OPTIONAL PADS to handle many other applications: dumping carboys, wire baskets, boxes; upending rolls, bales, and other objects from vertical to horizontal position.
- **Equal Arm Movement, Standard** — assures that the clamping pads grip the load at the same time. Side-shifting is available as an option.
- **180° Forward Tilt** — maximum operator control of dumping process and excellent visibility.
- **Save Time, Cuts Costs, Prevents Accidents and Injuries**
- **Versatile** — remove dumper pads to use as a standard fork clamp.



The Waldon Dump Upender is a fast, safe and efficient method for handling drums, boxes etc.



Waldon Dump Upender



Dumper-Upender*

Dual Hydraulic Function

SPECIFICATIONS

Model No.	Capacity w/Forks @ 24" L.C. (Lbs.)	Opening Range w/ Dumpers (In.)	Mounting ITA Hook	Fork Length (In.)	Lifting Capacity w/Dumpers (Lbs.)	Body Width (In.)	O.A.C.L. (In.)	C.G. (In.)	Weight (Lbs.)
DUC31A	3000	11-59	II	36	2000	35	32.5	9.0	700
DUC32A	3000	11-59	II	42	1800	35	38.5	12.0	725
DUC33A	3000	11-59	II	48	1500	35	44.5	14.0	750
DUC41A	4000	11-59	II	36	3000	36	33.5	8.6	830
DUC42A	4000	11-59	II	42	2500	36	39.5	11.0	850
DUC43A	4000	11-59	II	48	2000	36	45.5	13.0	870
DUC51A	5000	13-65	II	36	4000	40	34.5	9.6	1250
DUC52A	5000	13-65	II	42	3500	40	40.5	11.3	1270
DUC53A	5000	13-65	II	48	3000	40	46.5	13.5	1290

*Add 7 inches for opening range without dumper

Side-Shifting Dumper-Upender

Triple Hydraulic Function

SDUC31A	3000	11-59	II	36	2000	35	32.5	9.0	700
SDUC32A	3000	11-59	II	42	1800	35	38.5	12.0	725
SDUC33A	3000	11-59	II	48	1500	35	44.5	14.0	750
SDUC41A	4000	11-59	II	36	3000	36	33.5	8.6	830
SDUC42A	4000	11-59	II	42	2500	36	39.5	11.0	850
SDUC43A	4000	11-59	II	48	2000	36	45.5	13.0	870
SDUC51A	5000	13-65	II	36	4000	40	34.5	9.6	1250
SDUC52A	5000	13-65	II	42	3500	40	40.5	11.3	1270
SDUC53A	5000	13-65	II	48	3000	40	46.5	13.5	1290

*Add 7 inches for opening range without dumper

*Pressure regulator valve is recommended for all applications



201 West Oklahoma Ave. • Fairview, OK 73737
 580.227.3711 • Fax 580.227.2165
www.waldonequipment.com